

www.cobalttruck.com



QUOTATION

Quote Number: JS03040

Page 1 of 9

CUSTOMER: Cavender-Grande Ford Truck Center

CONTACT: Rocky Shoffstall

ADDRESS: Po Box 201210
San Antonio TX 78220

PHONE: (210) 661-4121

FAX/Email: Ref. City of Seguin /Wilcox Line Body

Quote Number: JS03040

Quote Rev: 0

Quote Date: 10/9/2025

Quote valid until: 10/23/2025

Salesperson: ralvarez

Quote Prepared By: Jsassman

Make: FORD	Model: F-750	Year: 2026	GVWR: 33000	Single/Dual: DRW
CA / CT: 84.0 /	Fuel Type: DIESEL	4X2 / 4X4: 4X2	Trans: AUTOMATIC	Cab Type: CREW CAB

QUANTITY	DESCRIPTION	PRICE EACH	AMOUNT
3	Wilcox Line body, Vanair-Genair, 2,000 lb. Elect/crane	\$190,100.00	\$570,300.00
3	Aluminum Service Body, as per customer specifications (listed below): - 134 inches long x 48 inches high x 94 inches wide - Designed for 84 inches with dual rear wheel axle. - (Sizes to be confirmed with layout drawing for approval prior to build) Body Dimensions: - 48 Inches - Compartment height - 20 Inches - Compartment depth - 54 Inches - Load space width Body Materials: - .125 Aluminum -complete body for extra strength - .125 Aluminum Smooth - Compartment tops Body Floor and Understructure: - .Plank flooring 1 1/8 thick aluminum- Floor - 3" Sills, 3" crossmembers Accessories: - Eberhard Whale Tail compression T-Handle door latches - All locks to be keyed alike - Gas Cylinder door holders on all vertically hinged doors (barn type horizontal) - Rubber rolled crown type fenders. (Installed with wheel cut-outs) - Automotive bulb type weather-stripping mechanically fastened to door frame with rounded corners. - Standard rope light (3/8" LED. 1" on center) compartment lights in all body compartments. (Not in top boxes) - Lights to have door switches. On when open, Off when closed - Rotary Master door locking system Paint: - Polyurethane white, interior & exterior of body and accessories. - Black chassis paint- protective undercoating		

345 W. Karcher Road
Nampa, ID 83687
Phone: 800-733-0342
Fax: 208-887-7794

1607 Industrial Road
Las Vegas, NV 89102
Phone: 888-258-9812
Fax: 702-385-9936

4691 FM 1516 N.
Converse, TX 78109
Phone: 855-587-7788
Fax: 210-301-2037

4620 E. Trent Avenue
Spokane, WA 99212
Phone: 800-572-4369
Fax: 509-535-4294

2800 Golden Triangle Blvd
Fort Worth, TX 76177
Phone: 682-990-6780
Fax: 208-887-7794



QUANTITY	DESCRIPTION	PRICE EACH	AMOUNT
	Streetside Compartmentation: 1st Vertical, 32" Wide x 48" High x 20" Deep - Top shelf with drawer unit 2nd Vertical, 24" Wide x 40" High x 20" Deep - Top shelf with drawer unit Horizontal Compartment, 50" Wide x 24" High x 20" Deep - 3 Point Eberhard Whale Tail compression T-Handle door latches with roller rods. - Automotive rotary catch & striker with pull handle on inside door. Streetside pull handle is Right Hand - Two (2) adjustable shelves each with divider slots on 3" centers installed on slotted channels each shelf will have Ten (10) adjustable dividers. Rear Vertical, 26" Wide x 48" High x 20" Deep - Two (2) adjustable shelves each with divider slots on 3" centers installed on slotted channels each shelf will have four (4) adjustable dividers. Curbside Compartmentation: 1st Vertical, 32" Wide x 48" High x 20" Deep - Top shelf with drawer unit 2nd Vertical, 24" Wide x 40" High x 20" Deep - Two (2) adjustable shelves each with divider slots on 3" centers installed on slotted channels each shelf will have four (4) adjustable dividers. Horizontal Compartment, 50" Wide x 24" High x 20" Deep - 3 Point Eberhard Whale Tail compression T-Handle door latches with roller rods. - Automotive rotary catch & striker with pull handle on inside door. Curbside pull handle is Left Hand - Two (2) adjustable shelves each with divider slots on 3" centers installed on slotted channels each shelf will have Ten (10) adjustable dividers. Rear Vertical, 26" Wide x 48" High x 20" Deep - Two (2) adjustable shelves each with divider slots on 3" centers installed on slotted channels shelf will have four (4) adjustable dividers. Tail shelf Rear Lighting: - 94" Wide 7-Lamp steel light bar installed at rear of tail shelf - Rubber mounted recessed rear lighting kit with harness - Stop/tail/turn lights, back up -LED Tail shelf: - 12 Ga. Hot rolled treadplate tail shelf 26 inches long X 94 inches wide		



QUANTITY	DESCRIPTION	PRICE EACH	AMOUNT
	x 6 inches high. 6 Inch structural steel channel full frame. - Through tunnel with dropdown access doors on both sides. - Full side and rear skirts to bottom of body - 12 gauge galvaneal Smooth - 3/4" crane reinforcement plate to be added to the top of the tail shelf on the StreetSide corner with the appropriate frame structure tied to the frame. - 3/4" crane reinforcement plate to be added to the top of the tail shelf on the StreetSide corner with the appropriate - Pull out 3 rung ladder step installed under curbside of tailahelf. Streetside and Curbside Tail Shelf Bulkheads: - 14" tall x 26" wide heavy-duty steel side bulkheads - constructed of 2" square steel tubing with panels of 12 gauge steel Tailgate: - Hinged tailgate 14" high X 73 1/8" wide heavy duty, swing down with latches. Removable Pipe Vise Holder: - Constructed from 2" reinforced tubing mounted to the curbside rear tail shelf with a lockable vise stand mount. Ladder Storage: - Ladder box with rear roller and lift up door with hasp latch. - Ladder box to accommodate a 10" ladder - No Exceptions, (Customer to provide dimensions) - Box designed for Uni-Strut mounting Curbside Top Mounted Basket: - 132" long X 13" high X 20" wide aluminum basket with corners notched for drainage. - One (1) lift up lid, 1/8" aluminum, opening to the cargo area - Two (2) Overcenter pad lockable - Gas assist door openers. - To be mounted on top of the ladder storage box - Speed liner on box assemblby StreetSide Top Mounted Basket: (Bolt-On / Installed) 132" long X 22" high X 20" wide aluminum basket with corners notched for drainage. One (1) lift up lid, 1/8" aluminum, opening to the cargo area - Two (2) Overcenter pad lockable latch. Part Number 30763 - Gas assist door openers. - To be mounted on top of the StreetSide compartment tops - Basket designed for Uni-Strut mounting - Basket and Uni-strut are both installed - Speed liner on box assemblby Punched Aluminum Headache Rack: - 53" wide x 31" High .125 aluminum Punched with a 1 1/2" x 1 1/2" angle frame cut at taper		



QUANTITY	DESCRIPTION	PRICE EACH	AMOUNT
	Grab Handles: - One (1) Rail type grab handle for installing on top of tail shelf to the rear of the body, curbside - One (1) Bolt-On Chrome grab handle for the side access of the body Hot Stick PVC Tube: - Aluminum Blaylock fixed cap on one end and drop down lockable door on other end. - 6 Inch x 120 Inches long tube mounted on the StreetSide load bed area against the wall - Mounted with U-Bolts and saddles at an angle with a drain hole in the bottom cap Cooler Shelf: - 30"L x 22"W shelf to mount atop of the Headache Rack - 3/16" Aluminum shelf top - 1/8" Aluminum gussets		
3	Install DRW line body as follows: - LED lights, Mud flaps & body mounting kit		
3	Connect body rope lighting to chassis system. - Rope lights and door switches in the body from manufacture - Pigtails will be supplied at the rear of the body, to hook into upfitter switches		
3	Samlex 2000 watt inverter installed as follows: - Mounted in RV1 compartment wall - 2000 watt output power - Pure sine wave output - Temperature controlled cooling fan		
3	Electrical power strip installed: - (5) 110v plugs - Built in surge protection - Installed next to inverter against the compartment wall		
3	Laptop computer stand (750) with adjustable mounting bracket - Mounted on passenger side floor - Adjustable telescoping stand - Rotating swivel arms to allow positioning for use in driver or passenger seat - Universal laptop mounting platform - 360 degree swivel - 85 degree tilt		
3	7- and 4-Pole trailer connector socket w/ mounting bracket (# HM40975) - Mounted at the rear of the body / bumper assembly		
3	Igloo 5 gallon water cooler with mounting bracket installed as follows: - Portable Plastic Water Cooler - 14" diameter x 20-1/2" high		



QUANTITY	DESCRIPTION	PRICE EACH	AMOUNT
3	- Yellow with red lid, includes lid-keeper cord - Storage rack with webbed strap with buckle		
3	Jerry gas can and holder, as per the following: - Holds 5 gallon steel Jerry can - Full metal construction for rugged use and abuse - Mounted in load bed area (curbside wall)		
3	Coneholder(s) installed on the front bumper with mounting bracket - (Qty. 2), One (1) each side of bumper		
3	Installation of 6" PVC pipe mounted on streetside of body area, - Mounted with U-bolts & saddles		
3	Storage box mounted in bed space of line body (next to bulkhead) - Trinity model 45 Job Site Tool Box (bolted to body floor) - Made from heavily reinforced steel with a matte rust-resistant powder coated finish - Top opening lid with (2) gas mounted lifts for easy open and close - 45" long (Interior box dimensions 41.5"W x 23.5"D x 18.5"H) - Forklift accessible with mounting feet at each corner		
3	Slide away retractable step system, Safety Fleet part # DB0202, - Mounted on rear tailshelf assembly, curbside - Welded steel construction - No rust, galvanized finish Red		
3	Install rear pipe vise holder, mounted under tailshelf assembly - Vise Mount (12"x 10"x 1/4" HR plate welded to a 18"L 2"x 2"x 1" square tube) - Painted white		
3	Reflective barricade tape: - Tailgate striping DOT pattern, mounted at the rear of the body		
6	(2) 110v GFI electric outlet mounted on right (CS) front of body & right (CS) rear of body wired to inverter with weatherproof cover		
3	Liftmoore 12V D. C. Powdered Electric Crane model L-21-7 VH ATB, installed as per the following: Specifications: - 6,000 Ft.-Lbs. Moment Rating - Maximum Capacity 2,000 Lbs. at 3 Ft. Load radius - Planetary Gear Winch with Permanent Magnet Motor - On / Off 12 Volt Electric - Remote Pendant Control 12.5 Ft. (removable) - Galvanized Aircraft Cable 3/16" x 25 Ft. (4,200 Lbs. Breaking Strength) - Travel Block w/swivel hook, For easy two part line hook up - Manual Rotation 360 Degree - Tapered Roller Bearings for ease of movement with a Manual Band Brake to control swing - Boom Elevation - Manual at two positions, 20 and 45 Degrees stows vertically for travel		



QUANTITY	DESCRIPTION	PRICE EACH	AMOUNT
	- Boom Extension - Manual from 3 Ft. to 5 Ft., optional to 7 Ft. - Anti-Two Block System, Needed when used in construction as per 1926.1441(d)(2) & 1926.1416(d)(3) - Mounting plate is 12" square with a 9.5" square bolt pattern		
3	Dedicated crane battery installed as follows: - Optima Group 31 battery - Battery storage box mounted in RR compartment		
3	Vanair Manufacturing Inc. Model GF66C2 GENAIR - 125CFM 100 PSI + 6.6kW Underdeck Systems installed complete as per the following: - V-Tec II Display, Controller and wiring harness - 125 cfm @ 100 PSI @ 1527 engine rpm / 1940 PTO shaft RPM - 160 CFM @ 100 PSIG @ 1920 engine rpm / 2435 PTO shaft RPM - This will have 6.6KW 120 Volt AC Power - PTO Muncie FR6Q-F1209-63B6 (1.27%) w/V-TEC & drive line - (Qty.2) Hose Reels model 8300 with OLP 3/4" x 50' hose, stops & couplings - (Qty. 2) Fuse, Velocity 3/4" check vales SCVH6 180-200 cfm		
3	Install Federal Signal SPIRE 220TP-AB LED beacon light (clear), as follows: - Weld mounting plate to top middle of cabguard / fan mounting brackets - Install LED beacon light on mounting plate and wire to chassis upfitter switch		
3	Anti-sail mud flaps, mounted behind rear wheels		
6	(Qty.4) Work lights mounted on the LH& RH side of the body - 40W LED Flood lights (Qty. 2) per side (front & rear) - Connected to chassis upfitter switches		
3	(Qty.8) Federal Signal Multi-strobe system installed: - FR7C2-BA strobe lights installed (blue/amber) - (2) Installed in the front (2) rear, (1) per side and (2) rear top boxes		
3	(1) 12v LED flood light installed on cab protector (cargo work light) - 40W LED Flood lights - Connected to chassis upfitter switches		
3	Ecco K7000B backup camera system installed as follows: - 7" LCD touch screen monitor with sunshade - Built-in speaker - 18 LED infrared camera		
3	Heavy duty rear buckplate installed as follows: - 3/4" steel rear face plate - 5/8" steel formed side gussets - Pintle hitch assembly, 30 ton - Receiver tube for pintle hook - 7-way trailer socket - Glad hands with dummy couplers - Safety chain loops		



QUANTITY	DESCRIPTION	PRICE EACH	AMOUNT
3	Electronic brake controller installed and wired to trailer socket		
3	Installation of rear grab handles on body - One each side of body-rear (Wilcox body supplied)		
3	5 lb. A-B-C fire extinguisher with bracket - Mounting location TBD at time of install		
3	Extension of chassis frame for installation of body (as necessary)		
3	Window tint added to chassis (DOT approved)		
3	Loose wheel lug indicators installed		
3	(3) 12v LED lights mounted underneath body as follows: - Mounted underbody streetside, curbside, and underneath rear of truck - Illuminates walking area around body - Wired to cab safety switch		
3	Speed Liner 1000 black, cargo area sides & bulkhead		
3	Speed Liner 1000 black, rear bumper / tailshelf		
3	Speed Liner 1000 black, top boxes		
3	(1) E-Track mounted on the curbside of the cargo wall		
3	CTE H.D. Aluminum 7-drawer unit installed as follows: - Mounted in LV1 compartment - (4)-4" and (3)-7" removable drawers - Aluminum construction - Patented motion latch drawer handles - 250 lb. capacity roller slides - Powder coated Hunter Green - (4) Divider kits (in 4" drawer) - Rubber liners in all drawers		
3	CTE H.D. Aluminum 7-drawer unit installed as follows: - Mounted in LV2 compartment - (1)-3", (3)-4", and (3)-7" removable drawers - Aluminum construction - Patented motion latch drawer handles - 250 lb. capacity roller slides - Powder coated Hunter Green - (3) Divider kits (in 4" drawers) - Rubber liners in all drawers		
3	CTE H.D. Aluminum 2-drawer unit installed as follows: - Fits RV1 compartment - (2)-7" removable drawers		



QUANTITY	DESCRIPTION	PRICE EACH	AMOUNT
	- Aluminum construction - Patented motion latch drawer handles - 250 lb. capacity roller slides - Powder coated Hunter Green - (No-Divider kits) - Rubber liners in all drawers		
Quote Total:			\$570,300.00

The following options may be added:

QUANTITY	DESCRIPTION	PRICE EACH	AMOUNT

Customer must fill out the information below before the order can be processed...

Accepted by:	
Date:	
P.O. number:	

TERMS AND CONDITIONS OF SALE:

- All sales are final and non-cancelable.
- Unless otherwise noted, payment terms are as follows with balance due prior to equipment shipping from a Cobalt facility or drop shipping from the manufacturer:
 - 35% down on sales < \$200,000
 - 50% down on sales > \$200,000
 - Credit cards may NOT be used for down payments.
- Orders will not be processed, and ship date will not be confirmed without receipt of down payment and purchase order.
- Credit card sales greater than \$2,000 will have a 3.5% service charge added to the total.
- Any invoice not paid within thirty (30) days of billing is subject to a 1.5% monthly interest charge.
- Quotation valid until above stated expiration date.
- PRICE ADJUSTMENT: The customer agrees to a price adjustment increase at the request of the supplier (Cobalt) in the event they can reasonably demonstrate market-driven material cost increases exceeding 3% of the current sell price after receipt of order despite reasonable efforts to reduce or eliminate such price increases. Upon any such request by supplier, supplier shall promptly deliver to customer such documentation as reasonably requested by customer to verify any purported cost increase related to the price adjustment. Within 7 days of such request and the customers receipt of reasonably sufficient verification demonstrating an actual associated price increase has been incurred in respect of the price adjustment, the customer shall review the impact of such unforeseen circumstances and, if appropriate, agree on updated pricing solely to reflect the allocation of any agreed upon price increases resulting directly from the price adjustment which shall be implemented immediately. On the day any new pricing is implemented, supplier will reflect the new agreed pricing and invoice for such adjustment, as applicable.
- Quoted price does not include any applicable F.E.T. (Federal Excise Tax), sales tax, and/or delivery charges.
- All quotations are contingent upon compliance with all the export laws and regulations of the United States. If any such law or regulation cannot be complied with, or if this equipment is prohibited from being exported at any time by the United States Government, this quotation and/or subsequent order(s) received or accepted will become null and void.
- Prices based upon total purchase and quantity quoted.

www.cobalttruck.com



QUOTATION

Quote Number: JS03040

Page 9 of 9

- Quoted price does not include any unforeseen obstructions or modifications. Customer will be contacted for approval prior to any modifications being made.
- Paint, if applicable, will be matched as closely as possible. An exact match cannot be guaranteed.
- Quote pending final weight distribution analysis based on chassis, equipment, and options.
- All in-stock units are subject to prior sale.
- Liability Disclaimer: Cobalt Truck Equipment shall not be liable for damage to customer provided vehicles due to causes beyond its reasonable control, including but not limited to acts of God, war, terrorism, civil unrest, government restrictions, strikes, natural disasters, weather related incidents or any other events that are unforeseeable and unavoidable. In the event of such an occurrence, Cobalt Truck Equipment shall notify the customer within 48 hrs.

345 W. Karcher Road
Nampa, ID 83687
Phone: 800-733-0342
Fax: 208-887-7794

1607 Industrial Road
Las Vegas, NV 89102
Phone: 888-258-9812
Fax: 702-385-9936

4691 FM 1516 N.
Converse, TX 78109
Phone: 855-587-7788
Fax: 210-301-2037

4620 E. Trent Avenue
Spokane, WA 99212
Phone: 800-572-4369
Fax: 509-535-4294

2800 Golden Triangle Blvd
Fort Worth, TX 76177
Phone: 682-990-6780
Fax: 208-887-7794