

Asphalt Zipper

480Xi

WITH ACCU-TRAK® WHEEL ASSIST



4' Cutting Width

Loader-Mounted Utility Trencher



with Dual-Frame ZipTec™ Enhanced Pulverizing System (PATENTED)
and Accu-Trak™ Wheel Assist

Packed with technology, yet surprisingly simple to operate, the 480Xi WA harnesses the power and productivity of much larger, self-propelled reclaimers into a very powerful, versatile and affordable loader attachment. Powered by a Cummins intercooled turbo-diesel (Tier 4 Final) engine, the 480Xi WA will pulverize up to 12-inch-thick asphalt in a single pass. The innovative upgrades and improvements throughout this new-generation Asphalt Zipper dramatically improve production in thicker asphalt, reliability and longevity of the machine, and ease of use. Opening utility trenches in asphalt, street patches, full road repairs and base stabilization are just a few of its many uses.



Custom tandem-axle trailer (optional) with quick-load guiding system, low center of gravity, convenient working deck and built-in custom toolbox, enables the 480Xi WA to be hauled behind a 1-ton pickup truck.

Specifications

Model	480Xi-200E WA	480Xi-260E WA
Engine	 Cummins 200 hp Turbo-Diesel Tier 4 Final	 Cummins 260 hp HOT-ROD Turbo-Diesel Tier 4 Final
Torque	685 ft·lb 929 N·m	730 ft·lb 990 N·m
Weight*	13,700 lbs 6214 kg	13,800 lbs 6260 kg
Cutting Width	48 in (42", 36", custom widths available) 1219 mm (1067, 914 mm, custom widths available)	
Cutting Depth	0 to 12 in 0 to 305 mm	
Host Vehicle	Compatible with loaders with gross operating weight of 20,000 lbs (9072 kg) or greater	

*Machine only, with Z-Pro™ X cutter head.

Asphalt Zipper reserves the right to change specifications at any time. U.S. Patent nos. 7036252, 7066555, 7144087, 8177456, 10086867. Other U.S. and international patents pending.



Toll-free: 888-ZIPPER-8 (947-7378)

310 West 700 South, Pleasant Grove, UT 84062
 Main: 801-847-3200 • Fax: 801-847-3250

www.asphaltzipper.com

Standard Features

Cutter Head	Z-Pro™ X
Cutting Bits	Double-carbide, bullet-head
Containment System	Dual-Frame ZipTec™ Enhanced Pulverizing System
Planetary	Fairfield Magnum-duty
Depth Control	Hydraulic (infinitely adjustable)
Rear Baffle	Infinitely adjustable, telescoping, hydraulic
Bit Hatch	Hydraulically powered , top access, with hydraulic shock absorption
Mounting System	Versa-Mount™ hydraulic, top-clamping Universal Coupler
Controls and Monitoring	<ul style="list-style-type: none"> Control Panel (on machine) Control Box (for host vehicle) Wireless Remote (for groundsmen)
Transport	Tows behind 1½-ton pickup on tandem-axle trailer.
Additional Features	<ul style="list-style-type: none"> ● Accu-trak™ Wheel Assist ● Built-in spray system ● Hydraulic belt tensioning ● Planetary cooling jacket ● Push fan under-hood cooling

Available Options

Side Shift and Tilt

Optional Mounting Systems:

- Quick Coupler
- Versa-Mount™ Quick Coupler

Water Supply Systems:

- Hitch Mount (150- or 300-gallon, for loaders)
- Boom Mount (150-gallon, for backhoes)
- Wheel Assist Mount (150- or 300-gallon)

Custom Trailer