



## ACCM6

### *SPECIFICATIONS FOR 6 COMPARTMENT*

### *CHASSIS MOUNT ANIMAL CONTROL UNITS*

#### ACCM6G To Fit Chevy, Ford, Dodge; (56" cab to axle-¾ Ton Vehicle Recommended)

**Overall Dimensions:** 80" wide, 52" tall overall, 106" long

**Storage Compartment:** 22" wide, 35" tall, 80" deep

**Animal Compartments:**

**Street Side:** Front 28"W x 35"H x 40"Deep

- Center 25"W x 26"H x 40"Deep
- Center 25"W x 26"H x 40"Deep

**Curb Side:** Front 28"W x 35"H x 40"Deep

- Center 25"W x 26"H x 40"Deep
- Center 25"W x 26"H x 40"Deep

**Construction:**

- Basic frame is 2" x 2" welded steel tubing with a Superstructure of 1" x 1" welded steel tubing
- All steel is hot dipped galvanized before covering
- The ceiling contains 4" foam insulation and the front, back and bottom contain 1" foam insulation to provide a 15-20 degree cooler temperature within each animal compartment
- Units are waterproof, corrosion resistant, and chew proof
- The interior and exterior material is 20 gauge stainless steel
- The ceilings consist of .050 aluminum with a roof of 1/8" aluminum diamond plate

- Doors are made with 12 gauge stainless steel and hinged from the front with a continuous stainless steel hinge
- Doors have positive locking tee handles, keyed alike
- Doors have adjustable louvered aluminum vents with perforated inside grilles
- Storage compartment floors are carpeted
- The storage compartment doors are solid (with no vents)
- Units are equipped with LED marker lights, LED stop and tail lights, LED dual backup lights, and four way flashers
- The body is mounted to the vehicle frame with eight (8) angle brackets
- 12 Volt Exhaust Fan, 800 CFM-The fan is installed in the roof of the unit to exhaust heat from each compartment
- Interior Lights-An LED interior light is installed in each compartment with all switches mounted on the dash of the vehicle
- 3-Swinging Partition-Swinging partitions are installed in compartments and opened to create a pass through compartment between each side of the unit.

### \*\*\*Optional Equipment\*\*\*

#### **Backup Alarm-Whelen Model #WBUA97**

**Secondary Safety Doors**—These doors are located inside the primary door and are constructed of 125 aluminum with ¾” holes punched for ventilation and a catch pole cutout.

**One Way Safety Doors**-These doors are located inside the primary door and are constructed of 1X2 aluminum. Each one way door will have two(2) spring loaded 125 aluminum panels to ease loading but still prevent escape until one way door is opened. Each one way door is equipped with positive latches and ¾” holes punched for ventilation.

**Top Luggage Rack**-This rack is installed on top of unit for additional storage. The rack is constructed of 1 ½ X 1 ½ square aluminum tubing welded.

**Emergency Strobe-Whelen Model #R2LPHDA**- measures 17” long and 3” high and 7” wide with (6)LIN6 Super LED Modules in amber with dash mounted switches.

**Air Conditioning System-Red Dot Model R-6100** Unit is 20,000 BTU with add on compressor to truck engine. (Rangers, S-10’s, Toyotas, etc are not adaptable to brackets for added compressors.)

**Auxiliary Heating-Red Dot Model R-254-4**- A 20,000 BTU directional air louvered heater.

**Patio Storage Bumper**-The bumper is constructed of steel and is 82” long and 15” wide, painted with automotive polyurethane paint, and has a storage compartment in the center.

**Step Bumper**-The bumper is constructed of stainless steel and is 82” long and 6” wide.

**Rubber Mats**-Constructed of ½” thick, chew proof rubber mats to fit the floor of the compartment.

**Rear Flood Lights** (2) 4 X 6 LED floodlights mounted on the rear of the unit.

**Dead Animal Pan**-This is available to fit the rear compartments only. It is constructed of aluminum and has four raised sides and handles on each end can be fitted in the rear compartments for loading dead animals.

**Pet Step**-Constructed of polypropylene, with a size of 70” L (35” L when folded) X 18” W with universal rubberized grips to fit any vehicle.

**Deerskin Lift System**-Slide out cage housed in curb side front compartment to assist in lifting large animals. Powered by an 1800# 12 volt, cable winch, the cage lowers to curb height and is capable of lifting 200 pounds.

**Dead Animal Box with Lift Gate**-Located in the rear center of the unit, with a electric lift gate capable of lifting 1000 pounds.

**Directional Light Bar-Whelen Model# TAM85-6** Lamp Super LED traffic advisor 47” Long, located on the rear of the unit, placed at center top to advise traffic of the vehicles location.

**Door Checks**-Mounted inside the cage attached to the primary door, used to hold the door in open position while loading/unloading animals.

**Digital Thermometer**-Mounted on dash of truck with the probe located inside animal unit to monitor temperature

while vehicle is in use.

**Rear Observation Camera** 5.6 inch LCD-TFT high resolution color monitor. Monitor has two audio/video inputs and a versatile mounting bracket. The high resolution reverse-image color camera has a 130 degree (diagonal) wide angle lens and 1-lux low light capability. It is water proof, includes an anti-glare sun shield, and one-way audio (from Camera to monitor). The Panasonic image sensor's resolution is rated at 380 lines and it is made of die-cast aluminum.

[Click Here To Request A Quote On This Item](#)